

ST
#4
4-1-03
60130-1179
00MRA0557

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Kalsi, et al.
Serial No.: 09/921,439
Filed: August 3, 2001
Priority: GB 0019017.3 Filed: August 4, 2000
Group Art Unit: 2834
Examiner: Unknown
Title: ACTUATOR

TRANSMITTAL OF CERTIFIED COPY


Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

With regard to the above-referenced patent application, enclosed is a Certified Copy of prior corresponding document GB 0019017.3 filed August 4, 2000.

Respectfully submitted,

CARLSON, GASKEY & OLDS, P.C.





Karin H. Butchko
Registration No. 45,864
400 W. Maple Road, Suite 350
Birmingham, MI 48009
(248) 988-8360

Dated: October 3, 2001

CERTIFICATE OF MAILING

I hereby certify that this Transmittal and accompanying documents are being deposited with the U.S. Postal Service as first class mail in an envelope addressed to Assistant Commissioner of Patents Washington, D.C. 20231 on October 3, 2001.


Raimi Blackerby



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 1 August 2001

The
**Patent
Office**



04AUG00 E558086-1 D01038
F01/7700 0.00-0019017.3

The Patent Office
Cardiff Road
Newport
South Wales
NP10 8QQ

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference JBJ/P300385GB

2. Patent application number
(The Patent Office will fill in this part)

0019017.3

4 AUG 2000

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Meritor Light Vehicle Systems (UK) Limited
Fordhouse Lane
Stirchley
Birmingham
West Midlands
B30 3BW
United Kingdom

7342876001

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

Actuator

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

WITHERS & ROGERS
Goldings House
2 Hays Lane
London
SE1 2HW

Patents ADP number (if you know it)

1776001 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (answer 'Yes' if:

a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

YES

Patents Form 1/77

Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 7 /
Claim(s) 2 / Q
Abstract
Drawing (s) 4 +4 +4 /

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) One /

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

J B Jones

Date

3/8/2000

12. Name and daytime telephone number of person to contact in the United Kingdom

John B Jones

0121 245 3900

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least six weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) *If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500 505.*
- b) *Write your answers in capital letters using black ink or you may type them.*
- c) *If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- d) *If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- e) *Once you have filled in the form you must remember to sign and date it.*
- f) *For details of the fee and ways to pay please contact the Patent Office.*

Actuator

The present invention relates to actuators, in particular power actuators for operating lock mechanisms of vehicle doors and other closures.

Such power operated lock mechanisms commonly form part of a central locking system of the vehicle whereby locking or unlocking of some or all doors or other closures can be effected from a single control station actuated from within or outside the vehicle as by a coded infra red or other remote input device. The lock mechanism and associated power actuator will provide for manual operation whereby respective doors can be locked and unlocked using a conventional internal sill button or other manually operated input element, and, maybe by manual operation of a cylinder or key controlled exterior lock.

An object of the present invention is to provide an improved form of actuator.

Thus according to the present invention there is provided an actuator including a rotatable worm wheel reversibly driveable by a motor, the worm wheel being operably connectable to an output element by a drive transfer device, the output element being moveable between a first and second position, in which the drive transfer device is operably disconnectable from the output lever to allow independent movement of the output lever.

According to another aspect of the present invention there is provided an actuator including a worm wheel being rotatable relative to a chassis of the actuator and being reversibly driveable by a motor, the worm wheel being operably connectable to an output element by a drive transfer device, the output element being moveable between a first and second position, in which a stop device acts operably between the worm wheel and chassis to stop the motor.

According to another aspect of the present invention there is provided an actuator including a rotatable worm wheel reversibly driveable by a motor, the worm wheel being operably connectable to an output element by a drive transfer device, the output element

being moveable between a first and second position, in which a stop device operates to stop the motor, in a forwards and reverse direction, the stop device including a forwards stop resiliently moveable relative to a reverse stop.

The invention will now be described, by way of example only with reference to the accompanying drawings in which:-

Figure 1 an exploded isometric view of part of an actuator according to the present invention;

Figures 2 to 12 are partial plan views of the actuator of figure 1;

Figures 13 to 15 are partial side elevation views of the actuator figure 1;

Figure 16 shows the extent of movement of various components of the actuator of figure 1; and

Figure 17 shows this drive transfer device of figure 1.

With reference to figure 1 there is shown an actuator 10 having a housing 12, a worm wheel 13, a stop device 16, a drive transfer device 18 and an output element 20.

Actuator 10 further includes a motor (not shown) having an output shaft (not shown) upon which is mounted a pinion (not shown) for engagement with the periphery 14A of the worm wheel 14.

Housing 12 includes a motor recess 22 in which sits the motor, and a worm wheel recess 24 in which sits the worm wheel 14.

Within the worm wheel recess is a first pivot pin 26. Furthermore the worm wheel recess includes first ramp 28 and second ramp 30 which are connected by plateau 32.

Housing 12 further includes a second pivot pin 34.

Worm wheel 14 includes a tooth periphery 14a (teeth of which are not shown for clarity).

Worm wheel further includes boss 36 having abutments 38 and 40.

A recess 42 is provided in a lower portion of the worm wheel and a hole 44 provides communication between the upper surface of the boss 36 and the recess 42.

The worm wheel further includes a central hole 46 in which is positioned first pivot pin 26 to allow the worm wheel to rotate within the worm wheel recess 24.

Stop device 16 includes first arm 48 and second arm 50.

A forward stop abutment 48A is provided on the end of first arm 48 and a reverse stop abutment 50A is provided on the end of second arm 50.

Stop device 16 includes a hole 52 for mounting on second pivot pin 34 to allow the stop device to pivot about second pivot pin 34.

A slot 54 is provided between the first and second arms and runs from the hole 52 in the general direction of the first pivot pin 26.

The stop device 16 is made from a resilient material and the slot 54 allows the forward stop abutment 48A to move slightly relative to reverse stop abutment 50A (see especially figure 7) wherein the slot 54 has opened slightly when compared with say figure 6.

The output element 20 includes a central hole 56 for pivotally mounting the output element on the first pivot pin 26.

The output element 20 further includes a first arm 58 which terminates in abutment 60 and a second arm 62 which includes a recess 64 and first and second ramps 66 and 68.

The drive transfer device 18 (shown schematically in figure 1, though in more detail in figure 17) includes a pin 70 having a lower shoulder 72 contained within pin housing 74. The drive transfer device 18 further includes a first spring 76 also contained within pin housing 74 and a second spring 78 mounted around the pin and within recess 42. It can be seen that the second spring 78 acts on pin housing 74 which in turn acts on shoulder 72 to bias the pin 70 downwards (when viewing figure 14) relative to the worm wheel. Furthermore the first spring 76 acts on a lower portion of the pin housing to bias the pin 70 upwards towards the output element 20 (see especially figure 15).

Operation of the actuator is as follows.

Consideration of figure 2 shows that the output element 20 at position B whilst abutment 38 of the worm wheel rest upon reverse stop abutment 50A of the stop device 16. In this position the drive transfer device 18 is aligned with recess base 24A thus allowing both the first spring 76 and second spring 78 to become extended (see for example figure 14). As such pin head 70A sits below the output element 20.

Actuation of the motor causes the worm wheel to move in a forwards (clockwise) direction when viewing figure 2, progressively through the position shown in figure 13, figure 3, figure 14, figure 4 to the position shown in figure 5.

It should be noted that the forwards and reverse directions of the motor have been chosen arbitrarily simply for ease of understanding of the invention.

Consideration of figure 13 shows that the worm wheel has rotated, carrying with it the drive transfer device, such that the pin housing 74 is caused to ride up second ramp 30 which results in second spring 78 becoming compressed and pin head 70 entering recess 64 of the output element 20.

Consideration of figure 3 shows that pin 70A has contacted an edge of recess 64 resulting in the drive transfer device 18 transferring the rotational movement of the worm wheel 14 to the output element 20. Note that output element 20 has moved in a clockwise direction from position B.

During this movement a lower edge of the pin housing 74 slides along plateau 32 thus ensuring that pinhead 70A is maintained in recess 64.

Consideration of figures 14 and 4 show different views of the actuator in the same position. It should be noted that pin housing has moved from plateau 32 down first ramp 28 and is opposite recess base 24a. This allows first spring 76 to extend thus lowering pin head 70A from within recess 64 and disengaging drive between the worm wheel and the output element. The first ramp 28 is arranged such that the output element 20 is rotated to position A, but no further. In this position abutment 60 of output element 20 has contacted the end of second arm 50 of the stop device causing it to rotate slightly in an anticlockwise direction (compare figure 2 and figure 4).

Continued operation of the motor causes the worm wheel alone to rotate to the position as shown in figure 5 whereupon abutment 40 contacts forward stop abutment 48A which stops the motor by causing it to stall momentarily until the power to the motor is stopped.

By driving the motor in a reverse direction the worm wheel 14, stop device 16, drive transfer device 18 and output element 20 can be returned to the position as shown in figure 2.

However, starting at the position shown in figure 5, it is also possible to manually move the output element 20 anticlockwise from position A as shown in figure 5 to position B as shown in figure 6, since at no time during this movement does pin head 70A engage recess 64.

Where power operation is required to move the output element 20 from position B to position A, the motor is actuated to drive the worm wheel in the clockwise direction. In particular consideration of such powered movement from position shown in figure 6 to the position shown in figure 7 shows that during this time the drive transfer device is always opposite recess base 24A and hence pin head 70A is in a lowered position and can pass under first arm 58 of output element 20.

Continued clockwise movement of the worm wheel causes the radially outer edge 36a to move past the end of second arm 50, causing the second arm 50 to spring radially outwards in doing so. Note that as shown in figure 7 the end of first arm 48 cannot move radially inwards since it is prevented from doing so by abutment 60 of the output element 20.

Continued clockwise movement of the worm wheel through the position shown in figure 8 to the position shown in figure 9 moves the output element to position A. Note that the position shown in figure 8 is identical to the position shown in figure 3 and the position shown in figure 9 is identical to the position shown in figure 5.

Consideration of figure 10 shows the output element 20 in position B (in fact the position shown in figure 10 is identical to the position shown in figure 2).

Whilst it is possible to manually move the output element 20 from position B to position A as described above it is also possible to move the output element 22 to a position intermediate position A and B (see figure 11).

Subsequent powered operation of the worm wheel in a forward direction (clockwise when viewing figure 12) causes the pin housing 74 to ride up second ramp 30 resulting in pin head 70A progressively projecting from the top surface from boss 36. However, because the output element 20 has been moved to an intermediate position pin head 70A rises outside recess 64. However, continued rotation of the worm wheel causes pin head 70A to engage first ramp 66 which results in a camming action forcing pin head 70A downwards and compressing first spring 76 until such time as pin head 70A aligns with

recess 64 whereupon first spring 76 can expand and push pin head 70A into recess 64, and this is inspite of fact that pin housing 74 is on plateau 32.


Thus even when the output element is manually moved to an intermediate position the actuator can still function properly and does not jam.



Considering of figure 16 shows the output element 20 in its extreme positions.

Claims

1. An actuator including a rotatable worm wheel reversibly driveable by a motor, the worm wheel being operably connectable to an output element by a drive transfer device, the output element being moveable between a first and second position, in which the drive transfer device is operably disconnectable from the output lever to allow independent movement of the output lever.
2. An actuator as defined in claim 1 in which one or more ramps effect the operable connection and/or disconnection of the drive transfer device with the output element.
3. An actuator as defined in claims 1 or 2 in which the drive transfer device is operably reconnectable with the output lever following independent movement of the output lever.
4. An actuator as defined in any preceding claim in which the drive transfer device includes a resiliently biased pin.
5. An actuator as defined in any preceding claim in which the drive transfer device operates in a direction substantially perpendicular to a plane of rotation of the worm wheel to operably connect and disconnect the worm wheel to the output element.
6. An actuator including a worm wheel being rotatable relative to a chassis of the actuator and being reversibly driveable by a motor, the worm wheel being operably connectable to an output element by a drive transfer device, the output element being moveable between a first and second position, in which a stop device acts operably between the worm wheel and chassis to stop the motor.
7. An actuator as defined in Claim 6 in which the stop device includes a forwards stop which operates to stop the motor in a forwards direction and also includes a reverse stop to which operates to stop the motor in a reverse direction.

8. An actuator as defined in claim 7 in which the stop device is moveable relative to the chassis to provide for the forwards and reverse stops.
9. An actuator as defined in claim 8 in which the stop device is moved by the output element.
10. An actuator as defined in any one of claims 7 to 9 in which the forwards stops is resiliently mounted relative to the reverse stop.
11. An actuator including a rotatable worm wheel reversibly driveable by a motor, the worm wheel being operably connectably to an output element by a drive transfer device, the output element being moveable between a first and second position, in which a stop device operates to stop the motor, in a forwards and reverse direction, the stop device including a forwards stop resiliently moveable relative to a reverse stop.





3/4

